



HMD 280-13



HMD 281-13

Circumaural, Closed Headphones

Based on the closed back, dynamic HD280 pro headphones, the HMD280-13 pro headset has been especially designed for communications in high-noise environments. Its dynamic, super-cardioid microphone has been optimised for close talking distances.

Features & Benefits

- Noise-compensated microphone with extremely low handling noise
- Microphone can be worn on either left or right-hand side
- Easily replaceable, single-sided coiled cable
- Very good attenuation of background noise
- Space-saving design with collapseible, rotating ear pieces
- Replaceable parts for long life
- Lightweight design
- Supplied complete with windshield for the microphone

Technical Data

Headphones

Transducer	Dynamic
Ear coupling	Circumaural, Closed
Frequency response	8 Hz - 25 kHz
Characteristic	SPL (at 1 kHz) 106 dB
THD	<0.2%
Nominal impedance	300 Ohms
Weight (without cable)	285 grams
Connection cable	single-sided coiled cable, OFC copper
Connector	3.5 mm stereo mini jack with 1/4" adapter

Microphone

Pickup Pattern	supercardioid
Transducer	Dynamic
Frequency Response	50Hz-13,500 kHz response
Sensitivity at 1kHz	1mV/Pa, 200ohms
Nominal impedance	200 Ohms

Connections

Connection cable	unterminated coiled cable min 1mm/max 3mm
------------------	--

Replaceable Accessories

Ear pads	Cat. No. 83320
Headband cushion	Cat. No. 83321
Cable	Cat. No. 82072
Windshield	Cat. No. 79252

Sennheiser Electronic Corporation, 1 Enterprise Drive, Old Lyme, CT 06371
 Telephone: 860-434-9190 Fax: 860-434-1759 Web: <http://www.sennheiserusa.com>
 Sennheiser Mexico: Av. Xola 613, PH6, Col. Del Valle 03100, Mexico, DF. Telephone: (525) 639-0956. Fax: (525) 639-9482
 Sennheiser Canada 221 Labrosse Ave, Pte-Claire, PQ H9R 1A3. Telephone: 514-426-3013. Fax: 514-426-3953
 Manufacturing Plant: Am Labor 1, 30900 Wedemark, Germany