

# EIP-2600

XGA DLP® Projector  
2600 ANSI Lumens

*Get the film-like imaging of DLP® technology with new BrilliantColor™ expanded-spectrum color reproduction in a classroom projector.*

- ▼ 2600 ANSI Lumens, 80% uniformity, and 2200:1 contrast ratio.
- ▼ True XGA resolution. SXGA+ through VGA and MAC compatible.
- ▼ Smart data compression/expansion, and video scaling.
- ▼ DVI-I input supports digital data, plus digital video w/HDCP.
- ▼ Accepts Composite, S, and Component Video, both 4:3 and 16:9.
- ▼ Compatible with HD input resolution up to 1080i.
- ▼ Convenient manual zoom (1.15X) and focus lens.
- ▼ Built-in image offset. Vertical digital keystone correction.
- ▼ Power Management and Eco mode help prolong lamp life.
- ▼ Selectable menu position and timeout. Auto input selection.
- ▼ Closed Caption. Wireless remote control.
- ▼ 3 Year\* Projector Warranty!




**EIKI**  
Projectors... and more!

# EIP-2600 2600 ANSI Lumens

## SPECIFICATIONS:

Screen Brightness	up to 2600 ANSI Lumens
Illumination Uniformity	80%
Size of Color Palette	16.7 Million
Contrast Ratio	2200:1
Projection Lamp	230 Watt UHP
Estimated Lamp Life	up to 4000 hours of use
Imaging System	0.55" in. DDR DLP® x 1
Screen Pixels	1024 x 768 in stripe configuration
Total Pixels	786,432 ((1024 x 768) x 1)
Lens Type	Manual Zoom and Focus
Lens Specs	Speed: f:2.5~2.6; FL: 0.803~0.925 in. (20.4~23.5 mm)
Lens Ratio	Zoom Max:Min: 1.15:1; Throw:Width: 1.64~1.97:1
Image Diagonal	40~300 in. (101.6~762 cm)
Image Width	2.6~20 ft. (0.79~6.1 m)
Throw Distance (tele-wide)	4.92~36.7 ft. (1.5~11.2 m)
Front Elevation	up to 8° up
Anti Keystone	Image starts 15.5% of image height above lens center
Vertical Keystone Correction	Digital: up to 80° up or down
Scanning Frequency	Auto: H Sync. 31-79kHz; V Sync. 50-85Hz
Dot Clock	108 MHz
Image Orientation	Normal, Reversed, Inverted
Local Control/Power Management	Full Function/Auto Shut-Off
Remote Control w/Mouse	Wireless (Infra Red) x 1
RS-232 Control Port	Mini DIN-9 x 1
Mouse (Page Up/Down) & Firmware Update Port	USB Type B x 1
TRIGGER terminal	DC 12V output
Computer Native Resolution	1024 x 768 (XGA)
Computer: Compatibility	SXGA+, SXGA, XGA, SVGA, VGA & MAC
Computer: Formats	1400 x 1050 through 640 x 480
Computer: Higher Resolutions	Displayed panned or Smart Compressed
Computer: Lower Resolution	Displayed normal or Smart Expanded
Video Compatibility	NTSC/PAL/SECAM/NTSC 4.43/PAL-M&N
Video HD Compatibility	480i/p, 540p, 576i/p, 720p, 1035i, 1080i
Video: Formats Supported	Normal 4:3 and Wide Screen 16:9
Video: Image Sizing	Video Scaling Technology
Signal Inputs:	
Digital Computer/Component w/HDCP	DVI x 1
Analog Computer/Component (w/optional adapter)	HD15 x 1
S Video	S-Video x 1
Composite video	RCA x 1
Audio Input	RCA x 2
Audio Input	Ministereore x 1
Signal Outputs:	
Computer/Component	HD15 x 1
Audio output	Ministereore x 1
Sound System-Amplifier	2 Watt (Mono)
Sound System-Speakers	1.1 in. (2.8 cm) x1
Fan Noise	as low as 29 dBA
Cabinet Size (HxWxD)	3.5 x 10.6 x 10.4 in. (89 x 270 x 265 mm)
Weight	6.4 lbs. (2.9 kg)
Packaged Size (HxWxD)	10.0 x 14.8 x 15.0 in. (255 x 375 x 382 mm)
Packaged Weight	13.2 lbs. (6.0 Kg)
Power Requirements	100-240V AC, 50/60Hz
Power Consumption	up to 303 W
Heat	up to 1140 BTU (287 KC)
Power Cord	6' (1.8 M) Type 3, Detachable
Electrical Safety Compliance	UL/cUL
Electromagnetic Compatibility	FCC Class B, CE Mark
Security Facilities	Kensington® Security Slot
Operating Temperature	41~95°F (5~35°C)
User Maintenance	Replace Lamp
UPC	4571194671629
Warranty: (to the original end-use customer)	
Projector:	3 Years/6000 Hour Use* (Parts/Labor to Correct Defects)
Lamp:	90 days (Failed Lamp Replaced Pro-Rata) *whichever occurs first




### INCLUDED ACCESSORIES:

Quick Set-up Guide. Owner's Manual on CD. AC Power Cord. Lens Cover. VGA type Computer Input Cable (Dsub 15~Dsub 15). Component Video Input Cable (Dsub 15~3-RCA). RS-232 Control Adapter (DIN~Dsub 9). Wireless Remote Control & Batteries (AA x 2).

### OPTIONAL ACCESSORIES:

Replacement Lamp. Mouse Cable (USB-A~USB-B). Ceiling Mount. Ceiling Post and Plate.

Talk to your EIKI Dealer... the "pro" in projectors.



### Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130

Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada, 310 First St.-Unit 2, P.O. Box 156, Midland, ON L4R 4K8

Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

<http://www.eiki.com>

# EIKI

Projectors... and more!

Specifications subject to change without notice.  
©2008 EIKI International, Inc. Printed in the USA. 10/15/08